

### 2019 West Pit Infill Drilling Results

Hole ID	From	To	Thickness	Au	Ag	Ag:Au	Au GxT	Average grade	
	feet	feet	feet	ppm	ppm		g/ft	cumulative feet	g/t Au
AR 216R	25	35	10	0.366	3	8.2	3.7		
	55	65	10	0.48	8	16.7	4.8		
	195	265	70	0.423	13	30.7	29.6		
	305	350	45	0.661	5	7.6	29.7		
	0	360					<b>67.8</b>	<b>135</b>	<b>0.502</b>
AR 217R	5	65	60	0.957	13.7	14.3	57.4		
	85	95	10	0.412	3.6	8.7	4.1		
	135	150	15	0.485	5.4	11.1	7.3		
	210	275	65	0.389	10.8	27.8	25.3		
	405	420	15	0.708	25.3	35.7	10.6		
	0	460					<b>104.7</b>	<b>165</b>	<b>0.635</b>
AR 218R	35	90	55	0.526	2.1	4.0	69.5		
	110	125	15	0.624	3.7	5.9	9.4		
	175	195	20	0.431	11.8	27.4	8.6		
	245	255	10	0.491	6.9	14.1	4.9		
	305	315	10	0.581	24.5	42.2	5.8		
	330	420	90	0.482	16.3	33.8	43.4		
	0	450					<b>141.6</b>	<b>200</b>	<b>0.708</b>
AR 219R	65	170	105	0.485	3.2	6.6	51		
	0	450					<b>51</b>	<b>105</b>	<b>0.486</b>
AR 220R	55	110	55	0.607	2	3.3	33.4		
	260	270	10	0.649	7.1	10.9	6.5		
	315	325	10	0.575	15.8	27.5	5.7		
	390	400	10	0.431	10.7	24.8	4.3		
	530	565	35	0.409	17.2	42.1	14.3		
	0	660					<b>64.2</b>	<b>120</b>	<b>0.535</b>
AR 221R	15	65	50	1.166	8.5	7.3	58.3		
	125	175	50	0.501	2.9	5.8	25.1		
	260	275	15	0.378	4.4	11.6	5.7		
	290	305	15	0.424	4.4	10.4	6.4		
	410	445	35	0.451	2.6	5.8	15.8		
	0	500					<b>111.3</b>	<b>165</b>	<b>0.675</b>
AR 222R	15	40	25	1.488	4.8	3.2	37.2		
	55	75	20	0.821	5.6	6.8	16.4		
	110	125	15	0.392	4	10.2	5.9		
	145	220	75	0.506	3.6	7.1	53.3		
	245	255	10	0.375	5.7	15.2	3.8		
	265	355	90	0.589	15.8	26.8	53		
	435	450	15	0.53	2.9	5.5	8		
	495	550	55	0.382	6.3	16.5	21		
	0	560					<b>198.6</b>	<b>305</b>	<b>0.651</b>
AR 223R	5	15	10	0.395	2.6	6.6	5.9		
	45	65	20	0.927	10.4	11.2	18.5		
	90	125	35	0.56	3.3	5.9	19.6		
	165	310	145	0.485	8.3	17.1	70.3		

	0	460					<b>114.3</b>	<b>210</b>	<b>0.544</b>
AR 224R	80	105	25	0.499	5.9	11.8	12.5		
	125	145	20	0.609	7.7	12.6	12.2		
	215	280	65	0.711	24.1	33.9	46.2		
	300	370	70	0.437	15.3	35.0	30.6		
	500	510	10	0.345	3.7	10.7	3.5		
							<b>92.5</b>	<b>190</b>	<b>0.487</b>
AR 225R	15	85	70	0.836	5.3	6.3	58.5		
	115	155	40	0.795	1.3	1.6	31.8		
	190	225	35	0.806	11.2	13.9	28.2		
	275	285	10	0.87	30.4	34.9	8.7		
	300	320	20	0.436	11	25.2	8.7		
	485	495	10	0.32	2.9	9.1	3.2		
	0	500					<b>139.1</b>	<b>185</b>	<b>0.752</b>
AR 226R	10	15	5	5.83	24.3	4.2	29.2		
	280	315	35	0.434	10.7	24.7	15.2		
	365	385	20	0.801	9	11.2	16		
	395	415	20	0.516	6.9	13.4	10.3		
	480	620	140	0.919	21.9	23.8	128.7		
	0	620					<b>199.4</b>	<b>220</b>	<b>0.906</b>
AR 227R	135	225	90	0.646	11.9	18.4	58		
	370	400	30	0.393	4.3	10.9	12		
	530	555	25	0.463	6.5	14.0	12		
	0	600					<b>82</b>	<b>145</b>	<b>0.566</b>
AR 228R	0	75	75	0.918	3.7	4.0	68.9		
	115	135	20	0.377	4.2	11.1	7.5		
	170	180	10	0.48	5.3	11.0	4.8		
	0	330					<b>81.2</b>	<b>105</b>	<b>0.773</b>
AR 229R	245	265	20	0.369	4.6	12.5	7.4		
	290	300	10	0.479	18.9	39.5	4.8		
	475	485	10	0.5	2.6	5.2	5		
							<b>17.2</b>	<b>40</b>	<b>0.430</b>
AR 230R	0	15	15	0.588	3.1	5.3	8.8		
	25	50	25	1.468	4.8	3.3	36.7		
	75	85	10	0.385	4.1	10.6	3.8		
	225	245	20	0.372	2.1	5.6	7.4		
	0	280					<b>56.7</b>	<b>70</b>	<b>0.810</b>
AR 231R	25	65	40	0.543	4.1	7.6	21.7		
	75	95	20	0.375	5.4	14.4	7.5		
	135	190	65	0.37	6.2	16.8	20.4		
	205	225	20	0.424	7.3	17.2	8.5		
	265	355	90	0.389	5.7	14.7	35		
	370	380	10	0.497	1.9	3.8	5		
	0	400					<b>98.1</b>	<b>245</b>	<b>0.400</b>
AR232R	0	25	25	0.468	1.7	3.6	11.7		
	45	55	10	0.378	3.8	10.1	2.9		
	125	155	30	0.611	4.1	6.7	18.3		
	280	295	15	0.592	6.3	10.6	8.9		

	320	340	20	0.737	17.9	24.3	14.7		
	0	360					<b>56.5</b>	<b>100</b>	<b>0.565</b>
AR 233R	0	70	70	0.737	2.3	3.1	55.3		
	140	155	15	0.351	4.6	13.1	5.3		
	235	275	40	0.403	3.6	8.9	16.1		
	345	375	30	0.701	6.6	9.4	21		
	440	450	10	0.51	2.5	4.9	5.1		
	465	500	35	0.618	9.9	16.0	21.6		
	0	700					<b>124.4</b>	<b>200</b>	<b>0.622</b>
AR 234R	35	50	15	0.338	2	5.9	5.1		
	175	205	30	0.429	7.4	17.2	12.9		
	0	400					<b>18</b>	<b>45</b>	<b>0.400</b>
AR 235R	40	80	40	0.688	5.5	8.0	27.5		
	145	155	10	0.303	3.5	11.6	3		
	190	205	15	0.98	4.8	4.9	14.7		
	220	270	50	0.503	4.2	8.3	25.1		
	300	310	10	0.446	6.3	14.1	4.5		
	0	320					<b>74.8</b>	<b>125</b>	<b>0.598</b>
AR 236R	30	50	20	0.41	0.9	2.2	8.2		
	120	130	10	0.496	0.4	0.8	5		
	175	215	40	0.574	1.4	2.4	22.9		
	0	450					<b>36.1</b>	<b>70</b>	<b>0.516</b>
AR 237R	0	40	40	0.399	2.7	6.8	16		
	50	60	10	0.475	4.1	8.6	4.8		
	80	115	35	0.311	1.9	6.1	11.6		
	140	155	15	0.383	2.8	7.3	5.7		
	165	195	30	0.618	15.3	24.8	18.5		
	260	330	70	0.512	9.6	18.8	35.9		
	390	435	45	1.388	16.6	12.0	62.5		
	0	565					<b>155</b>	<b>245</b>	<b>0.633</b>
AR 238R	0	40	40	0.358	1.4	3.9	14.3		
	70	95	25	1.623	17.3	10.7	40.6		
	165	200	35	0.809	5.7	7.0	28.3		
	265	445	180	0.79	10	12.7	142.2		
	460	475	15	0.428	7.2	16.8	15		
	0	600					<b>240.4</b>	<b>295</b>	<b>0.815</b>
AR 239R	15	30	15	1.8	11.7	6.5	27		
	120	145	25	0.873	0.64	0.7	21.8		
	210	225	15	0.577	1.1	1.9	8.7		
	240	265	25	0.604	2.2	3.6	15.1		
	350	360	10	0.413	1	2.4	4.1		
	420	430	10	0.403	8.2	20.3	4		
	0	450					<b>80.7</b>	<b>100</b>	<b>0.807</b>
AR 240R	10	105	95	1.031	8.8	8.5	97.9		
	120	125	5	2.952	11.8	4.0	14.8		
	150	215	65	0.419	9.8	23.4	27.2		
	225	235	10	0.562	7.6	13.5	5.2		
	245	275	30	0.41	9.1	22.2	12.3		
	310	345	35	0.398	3.5	8.8	13.9		

							<b>171.3</b>	<b>240</b>	<b>0.714</b>
AR 241R	15	30	15	0.986	4.5	4.6	14.8		
	45	60	15	0.351	1.6	4.6	5.3		
	70	95	25	0.453	1.4	3.1	11.3		
	145	295	150	0.68	13.7	20.1	102		
	320	370	50	0.405	4.2	10.4	20.3		
	395	405	10	0.46	11.5	25.0	4.6		
	0	450					<b>158.3</b>	<b>265</b>	<b>0.597</b>
AR 242R	0	110	110	0.535	4.3	8.0	58.9		
	130	170	40	0.37	4.6	12.4	14.8		
	180	225	45	0.339	5.7	16.8	15.3		
	0	300					<b>89</b>	<b>195</b>	<b>0.456</b>
AR 243R	0	15	15	0.336	6.2	18.5	5		
	110	120	10	0.387	6.9	17.8	3.9		
	155	265	110	0.475	5.4	11.4	52.3		
	280	300	20	0.49	14.2	29.0	9.8		
	425	435	10	0.495	8.3	16.8	5		
	465	475	10	0.347	3.4	9.8	3.5		
	490	520	30	0.322	4.6	14.3	9.7		
	0	520					<b>89.2</b>	<b>205</b>	<b>0.435</b>
AR 244R	170	335	165	0.589	7.2	12.2	97		
							<b>97</b>	<b>165</b>	<b>0.588</b>